



Go The Extra Yard.™



## MODEL: IS® 1500ZX

SPECIFICATIONS: Dated 7-30-2008

<b>TYPE:</b>	Mid mount, zero turn, twin stick steering rider with suspension.	<b>DECK:</b>	Floating, 10 gauge with lap welded corners, plug welded second top deck, full spindle width and metal deck shields.
<b>DECK SIZE:</b>	61"	<b>DISCHARGE CHUTE:</b>	Flexible rubber.
<b>ENGINE:</b>	28 HP Vanguard BIG BLOCK™ pressure lubrication, spin on oil filter, remote air cleaner.	<b>BELTS:</b>	Drive system - heavy-duty banded A-section belts to both pumps. Deck drive - one continuous loop B-section belt for spindles and deck drive.
<b>AIR CLEANER:</b>	Centrifugal, dry type w/replaceable element, two stage.	<b>SPINDLE PULLEYS:</b>	Split Steel.
<b>SUSPENSION:</b>	Four-wheel suspension with pivoting front axle, spring assemblies and rear-wheel coil-over-shock suspension.	<b>SPINDLES:</b>	Cast aluminum with 2.5" x 1" greaseable dual ball bearings and spindles.
<b>FUEL TANKS:</b>	Single, 6.0 gallon capacity 3.5" cap. Integrated cup holder.	<b>BLADES:</b>	0.25" thick, heat-treated, Marbain.
<b>DRIVE SYSTEM:</b>	Twin independent wheel motors and pumps with individual top mounted cooling 7" fans, 5 bolt wheel hubs, with 0.5 qt. spin on oil filter and reservoir mounted inside the frame.	<b>FRAME:</b>	1.5" by 2" 11-gauge rectangular tubing.
<b>SPEED:</b>	0 - 10 MPH forward 0 - 5 MPH reverse	<b>HOOR METER:</b>	Standard, activated with PTO.
<b>CONTROL SYSTEM:</b>	Twin fold over stick type, adjustable steering.	<b>SEAT:</b>	Adjustable, fore and aft, with fold down arm rests.
<b>PARKING BRAKE:</b>	Drum Style	<b>PAINT:</b>	Polyester powder coat paint. TGIC
<b>BLADE ENGAGEMENT:</b>	Electric clutch.	<b>WARRANTY:</b>	Two (2) years commercial warranty, parts and labor. (90 days on belts, blades, tires and brake pads)
<b>HEIGHT CONTROL:</b>	Foot activated, 0.25" increments, single pin adjust from 1.5" to 5".	<b>ROPS:</b>	Standard, folding roll-over protection with retractable seatbelt.
<b>TIRES:</b>	Drive: 22 x 11, 4 ply Caster - 13 x 5 x 6, 4 ply, tubeless, pneumatic.		