



Go The Extra Yard.™



MODEL: IS® 2000Z

SPECIFICATIONS: Dated 7-30-2008

TYPE:	Mid mount, zero turn, twin stick steering rider with four-wheel suspension.	TIRES:	Drive -22 x 10, 4 ply - (52") 22 x 11, 4 ply - (61") Caster - 13 x 5 x 6, 4 ply, tubeless, pneumatic.
DECK SIZE:	52", 61"	DECK:	Floating, 10 gauge with lap welded corners, plug welded second top deck, full spindle width and metal deck shields.
ENGINE:	25, 27 or 34 HP Kawasaki V-Twin, 26 HP Kawasaki LC, 27 HP Kohler, 30 HP Vanguard BIG BLOCK™, pressure lubrication, spin on oil filter, remote air cleaner.	DISCHARGE CHUTE	Flexible rubber.
AIR CLEANER:	Centrifugal, dry type w/replaceable element, two stage.	BELTS:	Drive system - heavy-duty banded A-section belt to each pump. Deck drive - one continuous loop B-section belt for spindles and deck drive.
SUSPENSION:	Front - independent with coil over, adjustable shocks. Rear - coil-over shocks	SPINDLE PULLEYS:	Split steel.
FUEL TANKS:	Twin, selectable, 6 gallon capacity (total 12 gallons) with individual fuel gauges. Outboard mounted. 3.5" cap. Integrated cup holder.	SPINDLES:	Greasable cast-iron (61") or greasable cast aluminum with 2.5" X 1" dual ball bearings (52")
DRIVE SYSTEM:	Twin independent wheel motors and pumps with individual top mounted 7" cooling fans, 5 bolt wheel hubs, 1/2 qt. spin on oil filter and reservoir and all hoses inside main frame.	BLADES:	0.25" thick, heat-treated, Marbain.
DRIVE AXLES:	1.25" tapered shaft.	FRAME:	1.5" by 2" 11-gauge rectangular tubing.
CONTROL SYSTEM:	Twin fold over stick type steering.	DECK MOUNTING:	All four corners to be suspension mounted.
SPEED:	0 - 10 MPH forward 0 - 6 MPH reverse	HOUR METER:	Standard, activates with PTO.
PARKING BRAKE:	Hand activated, drum.	SEAT:	Adjustable, fore and aft, with adjustable fold down arm rests and separate seat and back cushions; Suspension seat on 34 and 30 HP
BLADE ENGAGEMENT:	Electric clutch.	PAINT:	Polyester powder coat paint. TGIC.
HEIGHT CONTROL:	Foot activated, 0.25" increments, single pin adjust from 1.75" to 5".	WARRANTY:	Two (2) years commercial warranty, parts and labor. (90 days on belts, blades, tires and brake pads)
		ROPS:	Standard, folding roll-over protection with retractable seatbelt.