



MODEL: S200_X
SPECIFICATIONS: Dated 12/31/08

TYPE: Mid mount, zero turn, twin stick steering rider

DECK SIZE: 61" or 72" side discharge

ENGINE: 25 HP & 27 HP Kawasaki V-Twin, 27 HP Kohler, 32 HP Vanguard BIG BLOCK™; pressure lubrication, spin on oil filter, remote air cleaner.

AIR CLEANER: Centrifugal, dry type with replaceable element

FUEL TANKS: Twin, selectable, 5 gallon capacity (total 10 gallons) with individual fuel gauges. Outboard mounted. 3.5" cap. Integrated cup holder.

DRIVE SYSTEM: Twin independent Hydro Gear Pumps and Hydro Gear Wheel Motors with 7" fans. Five bolt wheel hubs, 1 qt. spin on oil filter and reservoir and all hoses inside main frame.

DRIVE AXLES: 1.25" tapered shaft

CONTROL SYSTEM: Twin fold over stick type steering

SPEED: 0 - 10 MPH forward.
0 - 5 MPH reverse.

PARKING BRAKE: Hand activated, disk type

BLADE ENGAGEMENT: Electric clutch

HEIGHT CONTROL: Foot activated, 0.25" increments, single pin adjust from 1.5" to 5"

TIRES: Drive - 24 x 12-12, 4 ply
Caster - 13 x 6-6.5, 4 ply, tubeless, pneumatic

DECK: Floating, 10-gauge with lap welded corners, plug welded second top deck, full spindle width and metal deck shields.

DISCHARGE CHUTE: Flexible rubber

BELTS: Pump drive - heavy-duty single B-section belt.
Deck drive - one continuous B-Section.

SPINDLE PULLEYS: Split steel

SPINDLES: Cast-iron 1" Shaft with top access grease fitting, 8" flange design adds strength to deck structure and greater dispersal of energy, 6-bolt flange for greater support of spindle to deck assembly.

BLADES: 0.25" thick, heat-treated, Marbain steel.

FRAME: One-piece - fully welded frame with main frame 2" by 2" tube type with ³/₁₆" wall thickness.

DECK MOUNTING: All four corners mounted to frame

HOURLY METER: Standard, activates with PTO

SEAT: Premium suspension seat package with lumbar controls standard on 27 HP Kawasaki & 32 HP Vanguard BIG BLOCK™ models. Adjustable, fore and aft, with adjustable fold down arm rests and separate seat standard.

PAINT: Polyester powder coat paint; TGIC

WARRANTY: Engine: Two (2) years manufacturer's warranty.
Transmission: Two (2) years manufacturer's warranty.
Balance of Machine: Two (2) years commercial warranty, parts and labor. (90 days on belts, blades, tires and brake pads)

ROPS: Standard, folding roll-over protection with retractable seatbelt.