



MODEL: SW20
SPECIFICATIONS: Dated 12/31/08

TYPE:	Intermediate walk mower with dual drive hydrostatic type transmission	DECK:	10 gauge with lap-welded corners, plug welded double top deck, full spindle width and metal deck shields.
DECK SIZE:	36" or 48" side discharge	QUICK ADJUST DECK:	1.5" to 4.5"
ENGINE:	13 HP (36") / 17 HP (48") Kawasaki; pressure lubrication and spin on oil filter	SPINDLES:	Cast aluminum with 2.5" X 1" dual ball bearings, top access grease fittings with weep holes.
FUEL CAPACITY:	5 gallons with 3.5" cap	SPINDLE PULLEYS:	Split steel
DRIVE SYSTEM:	Dual heavy-duty Hydro-Gear ZT2800 hydraulic transmission. Self-contained, charge pump design, steel cut gears, 1" axle shaft, spin-on oil filter and steel oil filter guard.	BLADES:	0.25" thick, heat-treated, Marbain
CONTROL SYSTEM:	Infinitely variable speeds, cruise control and maximum 3" travel on individual left/right turning and speed control handles. Foot activated neutral with independent steering override.	PAINT:	Polyester powder coat paint; TGIC
PARKING BRAKE:	Dynamic thru transaxles	WARRANTY:	Two (2) years commercial warranty, parts and labor (90 days on belts, blades, tires and brake pads)
BLADE ENGAGEMENT:	Electric clutch		
DUMP VALVES:	Twin independent, pull type with easy top access		
TIRES:	Drive - 18 x 8.5 (48"), 18 x 6.5 (36"), 4 ply Caster - 9 x 3.5, 4 ply, tube type with bolt together rims		
FRONT CASTERS:	1" shaft tapered roller bearings		